



# Under counter

Erogatore d'acqua naturale,  
gassata e fredda, microfiltrata  
e debatterizzata

*Room temperature, cold and sparkling  
microfiltered and debacterIALIZED water  
dispenser*



acqua temp. ambiente  
room temperature

acqua gassata  
sparkling water

acqua fredda  
cold water

# Home-Family

Il sottolavello Undercounter è disponibile nelle versioni con Telecomando (Wireless), Elettromeccanica ed Elettronica.

Silenzioso, compatto ed elegante, consente di avere sempre a disposizione una microfiltrazione d'acqua naturale, fredda e gassata.

L'installazione è semplice ed adattabile alle varie esigenze, anche in ambienti dove lo spazio talvolta può essere limitato.

E' gestito da un microprocessore che, attraverso sensori speciali, segnala il guasto e blocca il funzionamento, come nel caso di una perdita d'acqua.

Possiede un sistema di monitoraggio che, con l'ausilio della chip card, controlla la durata del filtro e segnala il momento della sostituzione.

Il basso consumo energetico lo rende un prodotto allineato alle normative più rigorose e l'esclusiva debatterizzazione UV garantisce l'igiene dell'acqua.

*Our Undercounter models are available in the Remote (Wireless), Electromechanical and Electronic versions. Compact and elegant, the Undercounter dispenser supplies cold, room temperature and sparkling microfiltered water. Very easy to install and noiseless, this dispenser, which can be adapted to meet any and all requirements, is perfect for any environment where space is a problem.*

*Undercounter is controlled by a microprocessor which, through special sensors, signals any malfunction and turns off the dispenser when dangerous conditions arise, such as leaks. It is equipped with a monitoring system that, through the use of chip card technology, controls the filter's service life and advises the user when it should be replaced. Thanks to its low power consumption the Undercounter water dispenser fully complies with the strictest regulations while UV debacterialization guarantees maximum hygiene.*

Undercounter  
*wireless*



Undercounter  
*electronic*



Undercounter  
*electro-mechanical*



Rubinetto non incluso  
Tap not included



Nella versione con bombola esterna ricaricabile, Undercounter è ideale anche per l'impiego nel settore bar-ristorazione.

*In the version with an external refillable cylinder, Undercounter is also ideal for use in bars and other food service businesses.*

COMPANY  
ECOLOGY  
TECHNOLOGY  
**HOME-FAMILY**  
OFFICE-SCHOOL  
RESTAURANT-BAR  
ACCESSORIES



# Technical features

UNDERCOUNTER	CHILLI	FILTERSTATION	WA&CO
220-230V - 50Hz - monofase 220-230V - 50Hz - monophase	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase	220-230V - 50Hz - monofase 220-230V - 50Hz - monophase
150W - 0.68A	70W - 0.84A	12W - 0.06A	1850W - 8.4A
10-32 °C	10-32 °C	10-32 °C	10-32 °C
Ermetico 65W Hermetic 65W	Ermetico 65W Hermetic 65W	=	Ermetico 65W Hermetic 65W
R134a 40g	R134a 40g	=	R134a 40g
Saturatore 4 l Saturator 4 l	=	=	Saturatore 4 l Saturator 4 l
Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C	Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C	=	Regolabile da 4 °C a 8 °C Adjustable from 4 °C to 8 °C
16 l/h	6.5 l/h (NO ACQUA GASSATA) 6.5 l/h (NO SPARKLING WATER)	1.7 l/m (NO ACQUA FREDDA E GASSATA) 1.7 l/m (NO COLD AND SPARKLING WATER)	16 l/h
150-400 kPa (1.5 - 4 bar)	150-400 kPa (1.5 - 4 bar)	150-400 kPa (1.5 - 4 bar)	200-400 kPa (2 - 4 bar)
INOX AISI 316L - 4 l	Serpentina 8m INOX AISI 316L - 4 l Coil length 8m INOX AISI 316L - 4 l	=	INOX AISI 316L - 4 l
Elettrovalvola di sicurezza Safety solenoid valve	=	=	Elettrovalvola di sicurezza Safety solenoid valve
350-600 kPa (3.5 - 6 bar)	=	=	350-600 kPa (3.5 - 6 bar)
Plastica Riciclabile Recyclable plastic	Lamiera zincata verniciata Painted zinc sheet	INOX AISI 304L Shiny	Plastica Riciclabile Recyclable plastic
Chip Card Filter Life Control	=	=	Chip Card Filter Life Control
18 kg	13 kg	4 kg	24 kg
240x365x370 mm	240x255x365 mm	280x100x380 mm	240x420x370 mm
	Sistema di raffreddamento a banco di ghiaccio ermetico con serpentina da 6m Hermetic ice bank cooling system (coil length 6m)	Autonomia pre-filtro 5.000 l Pre-filter capacity 5.000 l	Utilizzare esclusivamente cialde caffè ESE con diametro 42mm Use Ø 42mm ESE Coffee pod ONLY !!!